## MESSBOI 25 Length measuring device with mechanical counter

Mobile as a hand-held device or stationary use





Fig. 1 MESSBOI 25 with socket and hand grip

Fig. 2 MESSBOI 25 with roller cage unit

Fig. 3 MESSBOI 25 with hand grip

## **MESSBOI 25**

## • Mechanical length measuring device for winding material-Ø max. 25 mm

## **Functionality:**

The length measuring device is suitable for measuring the length of almost all types of cables and similar winding goods. The device can be used both as a hand-held device and as a stationary device. For portable use the screws have to be loosened by the socket and the length measuring device can be removed from the socket. Counter wheel detent and a clamp which can be opened to the side enables a convenient insertation of winding goods.

- Counter with reset button
- Continuously adjustable cable guiding
- Aluminium measuring wheel with vulcanized PUR coating
- Socket in the scope of delivery contained
- Non-slip hand grip
- Available with separately roller cage unit

Technical Data	MESSBOI 25	MESSBOI 25 conformity assessed*
Part No.	85101000	86101000
Measuring range	2 - 25 mm	2 - 15 mm
Error limit	+ / - 0,5 %	+ / - 0,5 %
Display of counter	9999,99 m	9999,99 m
LxWxH	approx. 120 x 160 x 350 mm	approx. 120 x 160 x 350 mm
Colour	aluminum / silver	aluminum / silver
Colour socket	RAL 7005 mouse grey	RAL 7005 mouse grey
Weight without socket	approx. 1,4 kg	approx. 1,4 kg
Weight socket	approx. 0,7 kg	approx. 0,7 kg

Equipment	Inlet and outlet roller cage unit
Part No.	85101001
Pollor cago unit for bottor quidance of the win	ling goods Poquired for MESSPOL25 conformity associated

Roller cage unit for better guidance of the winding goods. Required for MESSBOI 25 conformity assessed.

\*Conformity assessment of the lenght measuring device according module F1 with additional inlet and outlet roller cage is approved by German calibration authority. Valid for an unlimited period in the EEA. Conformity assessment has to be carried out in the manufacturing firm. Re-assessment after two years is not required, but maintenance by Kabelmat is recommended. **Only approved for useage in direct sales!** 

