Coil and spool unwinding machine

Perfect complement to processing machines



Fig. 1 SPULFIX 480 with open cover

SPULFIX 480

• Coil and spool unwinding machine

Functionality:

This machine is used as feeding device of all kinds of winding material to processing machines, such as Kabelmat take-ups or pre-assembling systems, e.g. automatic cutting machines, dismantling or stripping devices. The winding good can optionally be understood as coil or spool material. The rotation speed of the unwinder is controlled either by an accumulator or alternatively by additional set value taking the requested run-up and run-down time as well as the line speed into consideration.

Technical data	SPULFIX 480
Part No.	1823.000
Unwinding plate-Ø	max. 480 mm
Loading capacity	max. 20 kg
Accumulator capacity	3 m
Numbers of accumulator wheels	5/6
Winding material-Ø	max. 10 mm
Unwinding rotation speed	200 U / min
Pull force without additional weight	1,0 N
Pull force with weight (abt. 200 g)	1,5 N
Pull force with 2 weight (abt. 650 g)	1,7 N
Pull force with 3 weight (abt. 850 g)	2,0 N
LxWxH	approx. 1350 x 620 x 1860 mm
Weight	approx. 120 kg



Coil and spool unwinding machine

Basic equipment:

- Mobile basic machine as self-supporting, torsionally resistant weldment
- Holder for exchangeable dispensing plate of an outer diameter of up to 480 mm
- Mounted accumulator with a stroke of 500 mm and reverse-locked outlet roller
- Switch cabinet with operating elements
- · Additional outlet dancer for decreasing the starting pull force
- Built-in potentiometer for pre-setting the line speed
- Switch-off sensor for lower and upper accumulator position
- · Sensor for regulating the dispensing plate

Additional equipment:

• SPULFIX 480 horizontal unwinding plate for spools

Technical data		
Spool-Ø	max. 470 mm	
Spool width	max. 250 mm	
Plate-Ø	480 mm	
Core pin	Ø 16 x 200 mm	
Centering cone for bore-Ø	25 - 80 mm	
Spool weight	max. 20 kg	
Colour	zinc-plated	

• RINGFIX 480 horizontal unwinding plate for coils

Technical data	
Coil outer-Ø	max. 470 mm
Plate-Ø	480 mm
Height centering cones (3 pcs.)	250 mm
Core adjusting range	140 - 320 mm
Coil weight	max. 20 kg
Colour	zinc-plated



Fig. 2 SPULFIX 480 unwinding plate



Fig. 3 RINGFIX 480 unwinding plate



Fig. 4 SPULFIX 480 with closed cover

